

KIES UW OPTIturn® DRAAIBANK

	Vermogen	Centerhoogte	Centerlengte	Draaidiameter	Spilboring	Spilsnelheden	Klauwplaat 3 bekken	Onafhankelijke 4 bekken plaat	Vario Drive	Digit. snelheidsweergave	DPA Versie	Verlichting	230V	400V
TU1503V	0,45	70	250	140	11	120-3000	●		●				●	
TU2004V	0,6	100	300	200	21	150-2500	●		●	●			●	
TU2304	0,75	115	450	230	20	125-2000	●						●	
TU2304V	0,75	115	450	230	20	150-2200	●		●	●			●	●
TU2406	0,75	125	550	250	21	125-2000	●						●	
TU2406V	1,1	125	550	250	21	150-2500	●						●	
TU2506V	1,1	125	550	250	26	150-2500	●		●	●			●	
TU2807	0,85	140	700	266	26	150-2000	●						●	●
TU2807V	1,5	140	700	266	26	30-4000	●		●	●			●	
TU3008	1,1	150	800	300	36	150-2000	●						●	
TU3008V	1,5	150	800	300	36	30-3000								
TH3309/TH3309D	1,5	156	910	350	38	60-2000					●/-	●		●
TU3309V	2,2	145	910	350	38	12-2250			●	●	●	●	●	
TH3610/TH3610D	1,5	180	1000	356	52	70-2000					●/-	●		●
TH4010/TH4010D	1,5/2,4	205	1000	410	52	45-1800					●/-	●		●
TH4010V	4	205	1000	410	52	30-3000			●	●	●	●		●
D420x1000/1500	4,5	210	1000/1500	420	52	45-1800	●	●			●	●		●
TH4610/TH4615	5,5	230	1000/1500/2000	465	58	25-2000					●	●		●
TH4615V	7,5	230	1500	465	80	30-2000			●	●	●	●		●
TH5615/TH5620 TH5630	7,5	280	1500/2000/3000	560	80	25-1600					●	●		●
TH5620V	7,5	280	2000	560	105	25-1600			●	●	●	●		●
D660x2000/3000	7,5	330	2000/3000	660	105	25-1600	●	●			●	●		●
TU8020/TU 8030	7,5	330	2000/3000	660	105	25-1600	●				●	●		●